

IN THE CLAIMS

Please cancel claims 13-20 without prejudice or disclaimer as follows:

1. (Original) A system for partitioning and loading data in a low-powered communication device, the system comprising:

a general computing subsystem;

a modem computing subsystem;

a clock; and

a shared memory module for receiving a binary data, wherein the shared memory module may be accessed by the general computing subsystem and the modem computing subsystem independently, and wherein the general computing subsystem selectively activates the clock to the shared memory module to permit use of the shared memory module by the modem computing subsystem.

2. (Original) The system of claim 1 wherein the modem computing subsystem controls data processing in accordance with wireless communication protocols.

3. (Original) The system of claim 2 wherein the modem computing subsystem further comprises a mobile station wireless modem.

4. (Original) The system of claim 1 wherein the general computing subsystem further comprises a nonvolatile memory that stores information for generating the data.

5. (Original) The system of claim 4 wherein the general computing subsystem loads the data into the shared memory module.

6. (Original) The system of claim 4 wherein the general computing subsystem generates the data from compressed information stored in the nonvolatile memory.

7. (Original) A portable wireless communication device, the device comprising:
a nonvolatile memory;

a general computing subsystem having access to the nonvolatile memory;

a modem computing subsystem selectively enabled and disabled by the general computing subsystem; and

a first shared memory module independently accessible by the general computing subsystem and the modem computing subsystem, the first shared memory module being selectively enabled and disabled by the general computing subsystem, and wherein a first binary image is loaded in the first shared memory module from the nonvolatile memory by the general computing subsystem when selectively enabled.

8. (Original) The system of claim 7 wherein the first binary memory image comprises mobile station modem code sufficient to permit the modem computing subsystem to establish a wireless communication link and monitor a paging channel.

9. (Original) The system of claim 8, wherein the modem computing subsystem and the first shared memory module are enabled when the computing subsystem starts to monitor the paging channel, and the modem computing subsystem and the first shared memory module are disabled when not engaged in wireless communication.

10. (Original) The system of claim 8, further comprising a second shared memory module, wherein the second shared memory module is independently accessible by the general computing subsystem and the modem computing subsystem, wherein the second shared memory module

can be disabled by the general computing subsystem to save power, and wherein a second binary memory image is loaded in the second shared memory module from the nonvolatile memory by the general computing subsystem.

11. (Original) The system of claim 10, wherein the second binary memory image contains the mobile station modem code sufficient to operate a traffic channel.

12. (Original) The system of claim 11, wherein the second shared memory module is activated when the modem computing subsystem operates a traffic channel, and the second memory module is deactivated to save power when ceasing to operate the traffic channel.

13. (Cancel)

14. (Cancel)

15. (Cancel)

16. (Cancel)

17. (Cancel)

18. (Cancel)

19. (Cancel)

20. (Cancel)